DELOCK
we move the world

91604
EAN 4043619916047

3,5” USB2.0 Card Reader 24 in 1 Multipanel

Description
This card reader offer besides its classical function 2 USB 2.0 Ports, 1 FireWire port, microphone, audio In and Out The audio connections .are being lead outside over a slot bracket and connected on the sound card.

Specification
- Internal connection to USB 2.0 port (mainboard)
- Transfer rate Card-Readers max 480 Mbps
- 2 Slots for following card types:

CompactFlash(TM) (Typ I), CompactFlash(TM) (Typ II), IBM Microdrive, MagicStore, SmartMedia, MultiMediaCard, RS-MultiMediaCard, Secure Digital, Mini-Secure Digital, MemoryStick, MemoryStick MagicGate, MemoryStick Select, MemoryStick Duo, MemoryStick Duo MagicGate MemoryStick Pro, MemoryStick Pro MagicGate, MemoryStick Pro Duo, MemoryStick Pro Duo MagicGate, xD-Picture Card, TransFlash-Card with *Adapter, MultiMediaCard RS Dual Voltage, MultiMediaCard Dual Voltage, MMC mobile with *Adapter, MemoryStick Pro Duo Gaming *(Flash-Adapter not part of delivery content)

- USB powered; no external power supply
- Status signal for the card reader

System requirements
- USB2.0 and FireWire connection on the mainboard
- Windows 98, 98SE, NT4, 2000, ME, XP, Vista no driver required for Windows ME/XP

Package content
- card reader
- connentingcabel USB2.0, FireWire, Audio
- front panel black, beige, silver
- driver CD

Package
- Retail Box

www.delock.com

Alle hier aufgeführten Namen und Zeichen sind Eigentum des jeweiligen Herstellers. Druckfehler, Änderungen, Lieferzeiten & Irrtümer vorbehalten. I All brand names and products are registered trademarks of their respective companies. Misprints, changes, delivery times and errors excepted.